# 60cm 500 Series Integrated Insert Wall Rangehood



Providing effective extraction of steam, grease and odours, this sleek rangehood is perfectly hidden away in your cabinetry.

- Effective 780m3/hr airflow
- Seamlessly integrates into your kitchen cabinetry
- Dishwasher-safe aluminium filters for easy cleaning
- Energy-efficient LED lighting illuminates your cooktop

## DIMENSIONS

| Height | 325 mm |
|--------|--------|
| Width  | 492 mm |
| Depth  | 277 mm |

## **FEATURES & BENEFITS**

#### Seamless Fit

For a minimal look in your kitchen, this insert rangehood integrates seamlessly into cabinetry above your cooktop.

### **Effective Extraction**

Select between three fan speeds to ensure steam, odours and grease are extracted from your kitchen at the rate you need for your cooking.

## Easy Cleaning

The aluminium filters are easy to remove and dishwashersafe, for quick and simple cleaning.

## A Joy To Use

Thoughtful design features enhance your cooking experience, with responsive push-button controls and energy-efficient LED lighting to illuminate your cooktop.

#### Installed To Suit

This rangehood offers ducted or recirculated extraction, so you can choose the solution that best suits your kitchen.

## **SPECIFICATIONS**

| Accessories (included)                    |                |
|---|----------------|
| Aluminium filter                          | 793597         |
| Fan ratings                               |                |
| Maximum pressured air movement<br>EN61591 | 780 m³/hr      |
| Installation and cleaning                 |                |
| Dishwasher safe filters                   | 2              |
| Ducted                                    | Top extraction |
| Recirculation                             | Optional       |
| Performance                               |                |
| Extraction type                           | Surface        |
| Fan speeds                                | 3              |
| Filter type                               | Mesh           |
| Number of filters                         | 2              |
| Power requirements                        |                |
| Supply voltage                            | 220 - 240 V    |
| Product dimensions                        |                |
| Depth                                     | 277 mm         |

Haie

#### QUICK REFERENCE GUIDE > HPH60ILX2

| 325 mm  | 325 mmA PEACE OF MIND SALE492 mm24 Hours 7 Days a Week Customer Support |
|---------|---|
| 492 mm  |   |
|         | T 1300 729 948 Wwww.haier.com   |
|         |   |
| Push    |   |
|         |   |
| LED     |   |
|         |   |
| 2 years |   |
| 61700   |   |
| 61788   |   |
|         | 492 mm<br>Push<br>LED   |

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © 2020 Haier Inc. All rights reserved.

#### Other product downloads available at haier.com

- ✓ Specification Guide
- ↓ User & Installation Guide